

# FLORIDA BOATLIFTS

## SPECIFICATION CHART FOR PRO-LIFT ALUMINUM LIFTS

CAPACITY	6,000 lbs	8,000 lbs	10,000 lbs	13,000 lbs	16,000 lbs	20,000 lbs	24,000 lbs	30,000 lbs
"C" CHANNEL TOPS	7" @ 12'6"	7" @ 12'6"	7" @ 12'6"	7" @ 12'6"	7" @ 15'6"	7" @ 15'6"	7" @ 15'6"	8" @ 5'5"
I-BEAM BOTTOMS	6" @ 11'	6"H.D. @11'	8" @ 12'6"	8"H.D. @ 12'6"	10" @ 15'	10' @ 16'	10"H.D. @ 16'	12"H.D. @ 17'
PILINGS REQUIRED	4	4	4	4	6	6	6	8
WOOD BUNKS	3" x 8" x 12'	3" x 8" x 12'	3" x 8" x 12'	3" x 8" x 12'	3" x 10" x 14'	3" x 10" x 14'	DBL2"x12"x16'	DBL2"x12"x17'
ALUMINUM BUNKS	optional	optional	optional	optional	optional	optional	pending	pending
PVE GUIDE PIPE	3" @ 6'8"	3" @ 6'8"	3" @ 6'8"	3" @ 6'8"	3" @ 10'	3" @ 10'	3" @ 10'	3" @ 10'
STAINLESS CABLES	5/16" x 17'	5/16" x 31'	5/16" x 31'	5/16" x 31'	5/16" x 31'	5/16" x 45'	5/16" x 45'	3/8" x 52'
CABLE CONFIGURATION	1 part	2 part	2 part	2 part	2 part	3 part	3 part	3 part
DRIVE PIPE DIAMETER	2.375"	2.375"	2.375" H.D.	2.375" H.D.	2.375" H.D.	2.375" h.d.	2.375" h.d.	2.375" h.d.
CABLE WINDER DIAMETER	2.875"	2.875"	3.00" H.D.	3.00" H.D.	3.00" H.D.	3.00" high cap	3.00" high cap	5.00" high cap
WORM DRIVE RATING	3,500 lbs	3,500 lbs	3,500 lbs	3,500 lbs	7,000 lbs	7,000 lbs	7,000 lbs	n/a
DIRECT DRIVE WINCH	optional	optional	optional	optional	optional	optional	optional	standard
CROSS BRACES	optional	optional	optional	optional	standard	standard	standard	standard

LIFTS THAT ARE BUILT TO LAST